




# Titre de Votre Tuto

- Objet : du tuto 
- Niveau requis :   
[débutant](#), [avisé](#)
- Commentaires : *Contexte d'utilisation du sujet du tuto.* 
- Débutant, à savoir : [Utiliser GNU/Linux en ligne de commande](#), tout commence là ! 😊

## Introduction

what will happens if i close my laptop ?

*in my case it go for hibernation...*

**HandleLidSwitch=hibernate**

## Installation

edit that file (as root) :

`/etc/systemd/logind.conf`

```
# This file is part of systemd.
#
# systemd is free software; you can redistribute it and/or modify it
# under the terms of the GNU Lesser General Public License as published by
# the Free Software Foundation; either version 2.1 of the License, or
# (at your option) any later version.
#
# Entries in this file show the compile time defaults.
# You can change settings by editing this file.
# Defaults can be restored by simply deleting this file.
#
# See logind.conf(5) for details.

[Login]
#NAutoVTs=6
#ReserveVT=6
#KillUserProcesses=no
#KillOnlyUsers=
#KillExcludeUsers=root
#InhibitDelayMaxSec=5
#UserStopDelaySec=10
#HandlePowerKey=poweroff
#HandleSuspendKey=suspend
#HandleHibernateKey=hibernate
```

```
HandleLidSwitch=hibernate
#HandleLidSwitchExternalPower=suspend
#HandleLidSwitchDocked=ignore
#HandleRebootKey=reboot
#PowerKeyIgnoreInhibited=no
#SuspendKeyIgnoreInhibited=no
#HibernateKeyIgnoreInhibited=no
#LidSwitchIgnoreInhibited=yes
#RebootKeyIgnoreInhibited=no
#HoldoffTimeoutSec=30s
#IdleAction=ignore
#IdleActionSec=30min
#RuntimeDirectorySize=10%
#RuntimeDirectoryInodes=400k
#RemoveIPC=yes
#InhibitorsMax=8192
#SessionsMax=8192
```

## Utilisation

#HandleLidSwitch=lock – lock when lid closed.

#HandleLidSwitch=ignore – do nothing.

#HandleLidSwitch=poweroff – shutdown.

#HandleLidSwitch=hibernate – hibernate.

From:

<http://debian-facile.org/> - **Documentation - Wiki**

Permanent link:

<http://debian-facile.org/utilisateurs:tyzef:config:closing-laptop-behavior>



Last update: **16/01/2022 05:09**